



---

**SAFETY DATA SHEET**

---

**Section 1: IDENTIFICATION**

**Product Name:** #25LT1 Lacquer Thinner

**Product Code:** B1260

**MSDS Date:** December 18, 2014

Chemisphere Corporation  
2101 Clifton Ave  
St. Louis, MO 63139

**General Information:** 314-644-1300

**CHEMTREC:** 800-424-9300

**Section 2: HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW****GHS Classification:**

Flammable liquids (Category 2)

Skin irritation (Category 2)

Eye irritation (Category 2A)

Reproductive toxicity (Category 2)

Specific target organ toxicity - single exposure (Category 3), Central nervous system

Specific target organ toxicity - repeated exposure (Category 2)

Aspiration hazard (Category 1)

**GHS Labeling**

**Symbol:**

**Signal Word:** Danger

**Hazard Statements:**

Highly flammable liquid and vapor

Causes skin irritation.

Causes serious eye irritation

Suspected of damaging fertility or the unborn child

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

**Precautionary Statements:****Prevention:**

Do not breathe mist/vapors/spray.

Do not handle until all safety precautions have been read and understood.

Ground/bond container and receiving equipment.

Keep away from heat/sparks/open flames/hot surfaces-no smoking.

Keep container tightly closed.

Obtain special instructions before use.

Take precautionary measure against static discharge.

Use only non-sparking tools.

Use only outdoors or in a well-ventilated area.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

**Response:**

Get medical advice/attention if you feel unwell.

If exposed or concerned: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water shower.

If on skin: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Take off contaminated clothing and wash it before reuse.

**Storage:**

Store in a well-ventilated place. Keep cool. Keep container tightly closed.

Store locked up.

**Disposal:**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Potential Health Effects:** See Section 11 for more information

This product contains carcinogens or potential carcinogens as listed.

This material contains components that are considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Potential Environmental Effects:** See Section 12 for more information.

**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

No.	Component CAS REG. NO.	Amount %	OSHA		ACGIH	
			TWA	STEL	TWA	STEL
1	Toluene CAS #108-88-3	1-50	200 ppm	Not Avail	20 ppm	Not Avail
2	Light Hydrotreated Distillate CAS# 68410-97-9	1-50	5 mg/m3 MIST	Not Avail	5 mg/m3	Not Avail
3	Xylene CAS #1330-20-7	1-10	100 ppm	150 ppm	100 ppm	150 ppm
4	Ethylbenzene CAS # 100-41-4	1-10	Not Avail	Not Avail	100 ppm	125 ppm
5	Isopropyl Alcohol CAS #67-63-0	1-50	400 ppm	Not Avail	400 ppm	Not Avail
6	Methyl Ethyl Ketone CAS # 78-93-3	1-50	200 ppm	300 ppm	200 ppm	300 ppm
7	Acetone CAS #67-64-1	1-50	1,000 ppm	Not Avail	500 ppm	Not Avail

#### Section 4: FIRST AID MEASURES

##### Emergency first aid procedures by route of exposure:

- Inhalation:** If symptoms are experienced, remove source of contamination or move victim to fresh air. If affected person is not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
- Ingestion:**
- Skin:** Wash off for 20 minutes. Remove contaminated clothing, and any extraneous chemical. Get medical attention.
- Eyes:** Immediately flush eyes with water for at least 20 minutes while holding eyelids open. Remove contact lenses. Get medical attention.

**Note to physician:** In case of ingestion or massive inhalation, observe victim as an inpatient because of slow metabolism causes latent period of 24 hours between exposure and acidosis and blindness.

#### Section 5: FIRE FIGHTING MEASURES

**Flash Point (toluene):** Closed cup: 4°C (39°F). (Tagliabue (ASTM D-56))  
**Auto-ignition Temperature (toluene):** 536°C (997°F)  
**Lower Explosion Limit (toluene):** AP 1.2 %  
**Upper Explosion Limit (toluene):** AP 7.1 %  
**Flammability Classification:** Flammable Liquid Class IB

##### Suitable Extinguishing Media:

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

**Products of Combustion:** Upon decomposition this product may emit carbon dioxide, carbon monoxide, and/or low molecular weight hydrocarbons.

##### Fire Fighting Equipment/Instructions:

Avoid contact with the skin. A face shield should be worn. Use personal protective equipment. Wear self-contained breathing apparatus for fire-fighting if necessary

HAZARD	HMIS	NFPA
Toxicity	2	2
Fire	3	3
Reactivity	0	0

#### Section 6: ACCIDENTAL RELEASE MEASURES

**Personal Protection:** For large spills wear gloves, Tyvek suits, safety glasses, and appropriate NIOSH approved respiratory protection. Keep unnecessary personnel away. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.

**Special Properties:** Flammable Liquid! This material releases vapors at or below ambient temperatures. When mixed with air in certain proportions and exposed to an ignition source, its vapor can cause a flash fire. Use only with adequate ventilation. Vapors are heavier than air and may travel long distances along the ground to an ignition source and flash back. A vapor and air mixture can create an explosion hazard in confined spaces such as sewers. If container is not properly cooled, it can rupture in the heat of a fire.

**Environmental Precautions:** Prevent discharge to open bodies of water, municipal sewers, and watercourses.

**Method for Containment:** Absorb spilled liquid in suitable non-flammable inert material such as clay, vermiculite or diatomaceous earth. Control runoff and isolate discharged material for proper disposal. Approach release from upwind.

**Methods for Clean-up:** Ventilate area of leak or spill. Use spark-proof tools to sweep or scrape up and containerize in approved chemical waste container.

## **Section 7: HANDLING AND STORAGE**

### **Handling:**

Avoid contact with skin and eyes. Avoid inhalation of vapor or mist.  
Keep away from heat, sparks and flame. Use only with adequate ventilation.  
To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

### **Storage:**

Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame). Keep away from oxidizers. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## **Section 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION**

**Engineering Controls:** Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

### **Personal Protective Equipment (PPE)**

**Respiratory Protection:** Wear appropriate respirator when ventilation is inadequate.

**Eye/Face Protection:** Splash proof chemical goggles and face shield.

**Hand Protection:** Fluorinated rubber, impervious gloves, the breakthrough time of the selected glove(s) must be greater than the intended use period.

**Body:** Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

### **Other Protective Equipment:**

Facilities storing or utilizing this material should be equipped with eyewash and safety shower facilities.

This product contains:

Hexane, CAS NUMBER 110-54-3, OSHA TWA 500 ppm, ACGIH TWA 50 ppm

Heptane, CAS NUMBER: 142-82-5, OSHA TWA 500 ppm, ACGIH TWA 400 ppm

Cyclohexane, CAS NUMBER: 110-82-7, OSHA TWA 300 ppm, ACGIH TWA 300 ppm

**See section 3 for exposure limits.**

## **Section 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance, State</b>	Clear liquid
<b>Color</b>	Colorless
<b>Odor</b>	Not available
<b>pH (1%soln/water)</b>	Not Available
<b>Vapor Density (toluene)</b>	>3 (Air=1)
<b>Boiling Range (toluene)</b>	80 to 145°C (176 to 293°F)
<b>Vapor Pressure (toluene)</b>	AP 3.2 kPa (AP 24 mm Hg) (at 20°C)
<b>Melting Point</b>	Not Available

Freezing Point	Not Available
Flash Point (See Section 5)	
Flammability Properties (See section 5)	
Solubility (in water)	Very Slightly Soluble
Specific Gravity (toluene)	0.87 (Water = 1)
Evaporation Rate	Not Available
Octanol/Water partition coefficient (Kow)	Not Available
Auto-ignition temperature:	Not Available
Decomposition temperature:	Not Available
Viscosity:	Not Available

## Section 10: STABILITY AND REACTIVITY

**Stability:** This material is considered stable at ambient temperatures 70°C (21°C).

**Condition to Avoid:** Flames, sparks, electrostatic discharge, heat and other ignition sources.

**Incompatible Materials:** This product reacts with strong acid, strong bases, and oxidizing agents.

**Hazardous Decomposition:** Upon decomposition, this product evolves carbon monoxide, carbon dioxide, and/or low weight hydrocarbons.

**Hazardous Reactions:** This product will not undergo polymerization.

## Section 11: TOXICOLOGICAL INFORMATION

### ACUTE EFFECTS:

#### Component Analysis LD50

Toluene (108-88-3)  
48 Hr EC50 Daphnia magna: 5.46 - 9.83 mg/L [Static];  
48 Hr EC50 Daphnia magna: 11.5 mg/L  
Inhalation LC50 Rat 12.5 mg/L 4 h;  
Inhalation LC50 Rat >26700 ppm 1 h;  
Oral LD50 Rat 636 mg/kg;  
Dermal LD50 Rabbit 8390 mg/kg;  
Dermal LD50 Rat 12124 mg/kg

Acetone (67-64-1)  
Oral LD50 Rat: 5800 mg/kg  
LC50 Inhalation - rat - 8 h - 50,100 mg/m<sup>3</sup>  
LD50 Dermal - guinea pig - 7,426 mg/kg  
Skin - rabbit - Mild skin irritation - 24 h  
Eyes - rabbit - Eye irritation - 24 h

**Cyclohexane** (110-82-7)  
Oral (LD50): Acute: 12705 mg/kg [Rat] 813 mg/kg [Mouse]  
Dermal (LD) Acute 18000 mg/kg [Rabbit]

Xylene (1330-20-7)  
Inhalation LC50 Rat 5000 ppm 4 h;  
Inhalation LC50 Rat 47635 mg/L 4 h;  
Oral LD50 Rat 4300 mg/kg;  
Dermal LD50 Rabbit >1700 mg/kg  
Ethylbenzene (CAS # 100-41-4)  
LD50 Dermal - rabbit - 15,433 mg/kg

Isopropyl Alcohol (67-63-0)  
Inhalation LC50 Rat: 72.6 mg/L/4H  
Oral LD50 Rat: 4396 mg/kg  
Dermal LD50 Rat: 12800 mg/kg  
Dermal LD50 Rabbit: 12870 mg/kg

Methyl Ethyl Ketone (78-98-3)  
Oral LD50 2737 mg/kg  
Inhalation rat LC50 23,500 mg/m<sup>3</sup>/8-hr  
Skin rabbit LD50 6480 mg/kg

#### CHRONIC EFFECTS:

##### Component

Toluene (108-88-3)

**Carcinogenic Effects:** 3 - Not classifiable as to its carcinogenicity to humans (Toluene).

**Mutagenic Effects:** Not Available.

**Teratogenic Effects:** Not Available

**Reproductive Toxicity:** Damage to fetus possible.

Suspected human reproductive toxicant.

**Developmental Toxicity:** Reproductive effects in experimental animals and in long term chemical abuse situations.

**Target Organs:** Long-term overexposure to toluene has been associated with impaired color vision. Also, long-term overexposure to toluene in occupational environments has been associated with hearing damage. Skin, respiratory system, Central nervous system, Heart, blood, kidneys, lungs, liver, mucous membrane, brain, eyes, lens, or cornea. Lung irritation, chest pain, pulmonary edema, Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals.

Acetone (67-64-1)

**Carcinogenicity:** ACGIH A4 – Not Classifiable as a Human Carcinogen

**Neurotoxicity:** This product contains Acetone, a central nervous system target.

**Mutagenicity:** No information available for product.

**Reproductive:** No information available for product.

**Developmental:** No information available for product.

**Target Organs:** Acetone can target the respiratory system, eyes, CNS, kidneys, hematology.

Light Hydrotreated Distillate (68410-97-9)

**Carcinogenic Effects:** Not listed on the NTP, IARC, OSHA, or ACGIH lists of suspected/confirmed carcinogens.

**Mutagenic Effects:** Not Available.

**Teratogenic Effects:** Not Available

**Developmental Toxicity:** Not Available

**Target Organs:** Aspiration hazard if swallowed – can enter the lungs and cause damage. Harmful if inhaled and may cause delayed lung injury. Avoid contact with eyes, skin, and clothing. Material splashed into the eyes will irritate tissues. Unprotected exposure will cause skin dryness. **Skin** – tests on similar materials indicate acute irritation is expected to occur upon short-term exposure, chronic dermatitis on prolonged contact. **Ingestion** – Acute aspiration hazard. Tests on similar material indicate possibility of the following symptoms: headache, nausea, drowsiness, fatigue, pneumonitis, pulmonary adema, central nervous system depression, convulsions, and loss of consciousness. **Inhalation** – Tests on similar material indicate the possibility of the following symptoms: headache, nasal and respiratory irritation, nausea, drowsiness, breathlessness, fatigue, central nervous system depression, convulsions, and loss of consciousness.

Xylene (1330-20-7)

**Carcinogenic Effects:** A4 - Not classifiable for human or animal by ACGIH, IARC, or OSHA.

**Mutagenic Effects:** Xylenes have not demonstrated genotoxic activity in animals or humans and do not appear to be immunotoxic.

**Teratogenic Effects:** Not Available

**Developmental Toxicity:** Not Available

**Target Organs:** Nervous system, respiratory system. From the animal and human toxicology data, xylenes can be characterized as neurotoxic chemicals at moderate to high doses inducing symptoms in humans of dizziness, headache, nausea, and neuromuscular effects, speech impairment, and amnesia at high doses. Aspiration into the lungs of even a small amount may cause severe injury, since its low viscosity and surface tension will cause it to spread over a large surface of pulmonary tissue. Aspiration into the lungs of even a small amount may cause severe injury, since its low viscosity and surface tension will cause it to spread over a large surface of pulmonary tissue. **Eyes:** Irritation from vapors. Splash accidents have produced transient, superficial injury to the eye. **Skin:** May cause skin irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. **Inhalation** Central nervous system depression, narcosis, respiratory tract irritation & pulmonary edema. Severe exposure may cause death. **Ingestion** Aspiration hazard if swallowed. Can enter lungs and cause damage. May be fatal if swallowed. Central nervous system depression, a burning sensation in the oropharynx and stomach. Vomiting. **Potential Chronic Health Effects** Effects of chronic exposure to xylene are similar to those of acute exposure, particularly central nervous system effects (based on animal studies). **Overexposure/Signs/Symptoms:** Headache, tremors, apprehension, memory loss, weakness, dizziness, loss of appetite, nausea, ringing in the ears, irritability, thirst, anemia, mucosal bleeding, enlarged liver, and hyperplasia are reported when chronic inhalation of xylenes has occurred. Repeated contact with the skin can cause defatting dermatitis. Reversible eye damage, including vacuoles in the cornea and conjunctiva, has occurred with chronic xylene exposure.

Ethylbenzene (CAS # 100-41-4)

**Carcinogenic Effects:** 2B - Group 2B: Possibly carcinogenic to humans (Ethylbenzene)

**Mutagenic Effects:** Not Available.

**Teratogenic Effects:** Not Available

**Developmental Toxicity:** Not Available

**Target Organs:** Central nervous system depression, Nausea, Headache, Vomiting, Ataxia., Tremors

Isopropyl Alcohol (67-63-0)

**Carcinogenicity:** No known hazards

**Mutagenicity:** Not available.

**Reproductive:** Not available.

**Developmental:** Not available.

**Target Organs:** skin, eyes, CNS, and respiratory system. **Eye:** Contact with eyes may cause redness and pain. **Skin:** Contact with skin may cause dry skin. **Inhalation:** Inhalation of this material may cause: cough, dizziness, drowsiness, headache, sore throat, abdominal pain, labored breathing, nausea, vomiting, and unconsciousness. **Ingestion:** Ingestion of this material may cause: cough, dizziness, drowsiness, headache, sore throat, abdominal pain, labored breathing, nausea, vomiting, and unconsciousness.

Methyl Ethyl Ketone (78-93-3)

**Carcinogenicity:** Not listed by IARC, ACGIH, NTP, or OSHA.

**Neurotoxicity:** No information available

**Mutagenicity:** No information available

**Reproductive:** No information available

**Developmental:** No information available

**Target Organs:** Central nervous system depression, Gastrointestinal disturbance, narcosis. Prolonged exposure may cause central nervous system effects. Central nervous system depression, Gastrointestinal disturbance, narcosis May cause drowsiness or dizziness.

**Inhalation** May be harmful if inhaled. Causes respiratory tract irritation. Vapors may cause drowsiness and dizziness.

**Skin** May be harmful if absorbed through skin. Causes skin irritation.

**Eyes** Causes eye irritation.

**Ingestion** May be harmful if swallowed.

## Section 12: ECOLOGICAL INFORMATION

### Ecotoxicity: Toluene (108-88-3)

96 Hr EC50 *Pseudokirchneriella subcapitata*: >433 mg/L;  
72 Hr EC50 *Pseudokirchneriella subcapitata*: 12.5 mg/L [static] mg/L [flow-through] (1 day old);  
96 Hr LC50 *Pimephales promelas*: 12.6 mg/L [static];  
96 Hr LC50 *Oncorhynchus mykiss*: 5.89-7.81 mg/L [flowthrough];  
96 Hr LC50 *Oncorhynchus mykiss*: 14.1- 17.16 mg/L [static];  
96 Hr LC50 *Oncorhynchus mykiss*: 5.8 mg/L [semi-static];  
96 Hr LC50 *Lepomis macrochirus*: 11.0-15.0 mg/L [static];  
96 Hr LC50 *Oryzias latipes*: 54 mg/L [static];  
96 Hr LC50 *Poecilia reticulata*: 28.2 mg/L [semi-static];  
96 Hr LC50 *Poecilia reticulata*: 50.87-70.34 mg/L [static]  
48 Hr EC50 *Daphnia magna*: 5.46 - 9.83 mg/L [Static];  
48 Hr EC50 *Daphnia magna*: 11.5 mg/L

### Ecotoxicity: Acetone (67-64-1)

96 hour LC50 *Oncorhynchus mykiss*: 5540 mg/L (static)  
96 hour LC50 *Pimephales promelas*: 6210 mg/L [flow through]  
96 hour LC50 *Lepomis macrochirus*: 8300 mg/L [static]  
15 min EC50 *Photobacterium phosphoreum*: 14,500 mg/L  
48 Hr EC50 water flea: 0.0039 mg/L  
48 hour EC50 water flea: 12,700 mg/L [static]  
48 hour EC50 *Daphnia magna*: 12,600 mg/L

### Ecotoxicity: Xylene (1330-20-7)

96 Hr LC50 *Pimephales promelas*: 13.4 mg/L [flow-through];  
96 Hr LC50 *Oncorhynchus mykiss*: 2.661-4.093 mg/L [static];  
96 Hr LC50 *Oncorhynchus mykiss*: 13.5-17.3 mg/L;  
96 Hr LC50 *Lepomis macrochirus*: 13.1-16.5 mg/L [flow -through];  
96 Hr LC50 *Lepomis macrochirus*: 19mg/L;  
96 Hr LC50 *Lepomis macrochirus*: 7.711- 9.591 mg/L [static];  
96 Hr LC50 *Pimephales promelas*: 23.53-29.97 mg/L [static];  
96 Hr LC50 *Cyprinus carpio*: 780 mg/L [semi-static];  
96 Hr LC50 *Cyprinus carpio*: >780 mg/L;  
96 Hr LC50 *Poecilia reticulata*: 30.26-40.75 mg/L [static]  
48 Hr EC50 water flea: 3.82 mg/L;  
48 Hr LC50 *Gammarus lacustris*: 0.6 mg/L  
48 Hr EC50 water flea: 3.82 mg/L;  
48 Hr LC50 *Gammarus lacustris*: 0.6 mg/L

### Ecotoxicity: Isopropyl Alcohol (67-63-0)

96 Hr EC50 *Scenedesmus Subspicatus*: >1000 mg/L  
72 Hr EC50 *Scenedesmus subspicatus*: >1000 mg/L  
96 Hr LC50 *Pimephales promelas*: 9640 mg/L [flow through]  
96 Hr LC50 *Pimephales promelas*: 94900 mg/L [flow through] (29 days old)  
96 Hr LC50 *Pimephales promelas*: 61200 mg/L [flow through] (31 days old)  
5 min EC50 *Photobacterium phosphoreum*: 35390 mg/L  
48 Hr EC50 *Daphnia magna*: 13299 mg/L

### Ecotoxicity: Methyl Ethyl Ketone (78-98-3)

Fish LC50/960hour > 100 mg/l  
mortality NOEC - *Cyprinodon variegatus* (sheepshead minnow) - 400 mg/l - 96 h  
LC50 - *Pimephales promelas* (fathead minnow) - 3,130 - 3,320 mg/l - 96 h  
LC50 - *Daphnia magna* (Water flea) - > 520 mg/l - 48 h  
EC50 - *Daphnia magna* (Water flea) - 7,060 mg/l - 24 h



### Section 13: DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations.

### Section 14: TRANSPORT INFORMATION

**Proper Shipping Name:** Paint related material

**Hazard Class:** 3

**Identification No.:** UN1263

**Packing Group:** II

**Label:** Flammable

### Section 15: REGULATORY INFORMATION

**TSCA Inventory** This product and/or its components are listed on the Toxic Substances Control Act (TSCA) inventory.

**SARA 302/304** The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to Subparts 302 and 304 to submit emergency planning and notification information based on Threshold Planning Quantities (TPQs) and Reportable Quantities (RQs) for "Extremely Hazardous Substances" listed in 40 CFR 302.4 and 40 CFR 355. No components were identified.

**SARA 313:** Toluene (CAS #108-88-3) Hexane, Cyclohexane, Xylene, ethylbenzene

**CERCLA** The Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) requires notification of the National Response Center concerning release of quantities of "hazardous substances" equal to or greater than the reportable quantities (RQ's) listed in 40 CFR 302.4. As defined by CERCLA, the term "hazardous substance" does not include petroleum, including crude oil or any fraction thereof which is not otherwise specifically designated in 40 CFR 302.4. Chemical substances present in this product or refinery stream that may be subject to this statute are: Toluene [CAS No.: 108-88-3] RQ = 1000 lbs. (453.6 kg), Acetone [CAS No. 67-64-1] RQ = 5,000. Xylene [CAS No.: 1330-20-7] RQ = 100 lbs (45.3 kg), ethylbenzene [CAS No.: 100-41-4] RQ=1,000lbs Methyl Ethyl Ketone RQ = 5,000lbs

**SARA 311/312 Hazard** The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires facilities subject to this subpart to submit aggregate information on chemicals by "Hazard Category" as defined in 40 CFR 370.2. This material would be classified under the following hazard categories: Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard, Fire Hazard

#### Additional Regulatory Remarks

Federal Hazardous Substances Act, related statutes, and Consumer Product Safety Commission regulations, as defined by 16 CFR 1500.14(b)(3) and 1500.83(a)(13): This product contains Toluene which may require special labeling if distributed in a manner intended or packaged in a form suitable for use in the household or by children. Precautionary label dialogue should display the following: **DANGER: Contains Toluene! Harmful or fatal if swallowed! Call Physician Immediately. Vapor Harmful! KEEP OUT OF REACH OF CHILDREN!**

**California Prop 65:** Toluene developmental toxicity, Ethylbenzene cancer toxicity

### Section 16: OTHER SUPPLEMENTAL INFORMATION

Prepared by: Chemisphere Corp. on 12/18/14

Disclaimer:

The information and recommendations contained in the Safety Data Sheet (SDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

Chemisphere, however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will Chemisphere be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE, ARE MADE BY CHEMISPHERE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance which is the subject matter of this SDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.